Auger Kit



DESCRIPTION

The 0212 Soil Sampler allows the extraction of intact soil cores. A core 3-1/2" (8.9 cm) in diameter is extracted and held in a brass cylinder. The cylinder and the soil sample can then be placed in a pressure plate extractor or Tempe cell apparatus and the water-holding characteristics of the sample can be determined. The cylinder can be used to provide a sample of known volume, allowing the bulk density to be determined. The sampler is supplied with two wedge coring tips, hammer, spanner wrench for replacing coring tips, and six brass cylinders; two 6 cm long and four 3 cm long. The model 0212 soil core sampler is idea for the collection of large 3.5" diameter undisturbed soil core samples for bulk density measurement.



DESCRIPTION

Ergonomic Auger Set for soils.

extensions connections for sampling down to 5 meters depth.

Includes:

- 4 types of Dutch augers (clay-, sand-, coarse sand and combination type).
- 1 Bucket auger.
- 1 Spiral auger.
- 1 Gouge auger.

All augers have Bayonet Type handle &

- 1 Stony soil auger
- Aluminum transport case.

This Instrument is manufactured by our principle company

Soil Moisture Corp - USA

SPECIFICATION

- Augers are unpainted.
- Sampling Hole depth: down to 5 meters
- Weight: 63.95 lbs.
- Dimensions: 40X20X10 inches

APPLICATION

- Soil Sampling
- **Environmental Monitoring**
- Soil Physics.

OTHER MODELS

- 1. SANDY SOILS AUGER, DUTCH STYLE || 7 CM & 10
- 2. LOAM SOILS AUGER . DUTCH STYLE || 4 CM TO 10 CM
- 3. SOIL AUGERS, RIVERSIDE STYLE |||| 5 CM TO 10 CM
- 4. ONE PIECE AUGERS & SAMPLERS || 2.5 CM TO 7 CM DIAMETER.
- 5. SIZING AUGERS, FOR HOLE **BOTTOM SQUARING 6 CM &** 10 CM
- 6. BOREHOLE PREP. KITS
- 7. GOUGE AUGER KITS

Contact info



Monitoring MENA

Insight into instrumentations

(962) 5353-2091

PO Box 1100 Salt

Post Code 19110 JORDAN

sales@monitoring-mena.com

www.monitoring-mena.com